

METRALINE ISO^{CHECK} Insulation Measuring Instrument

3-349-690-03
4/5.21

- **Insulation resistance measurement** with test voltages of 50 to 1000 V
- **Voltage measurement** up to 600 V
- **Measurement of surge protection devices** with test voltages of 50 to 1000 V
- Table of common varistors can be displayed
- Digital display, backlit color OLED display
- Indication of dangerous touch voltage
- LED for measurement point illumination
- Patented means of securing test probes
- **Compact and rugged:**
For service calls under harsh conditions and laboratory use



Ramp Function



Measurement Results




Table Display



Applications

- Measurement of insulation resistance at voltage-free devices and systems, up to 1000 V depending upon variant
- Measurement of surge protection devices, up to 1000 V depending upon variant
- Checking of test objects for absence of voltage

Applicable Regulations and Standards

IEC 61010-1/-031 DIN EN 61010-1/-031 VDE 0411-1/-031	Safety requirements for electrical equipment for measurement, control and laboratory use Part 1: General requirements Part 31: Safety requirements for hand-held probe assemblies for electrical measurement and test
IEC 61557-1/-2 DIN EN 61557-1/-2 VDE 0413-1/-2	Electrical safety in low voltage distribution systems up to 1000 V AC and 1500 V DC – Equipment for testing, measuring or monitoring of protective measures Part 1: General requirements Part 2: Insulation resistance measuring instruments
IEC 61326-1 DIN EN 61326-1	Electrical equipment for measurement, control and laboratory use – EMC requirements Part 1: General requirements
DIN EN 60529 VDE 0470-1	Degrees of protection provided by enclosures (IP code)

Characteristic Values

Measurement of Insulation Resistance

Nominal Range per EN 61557-2: 0.100 MΩ – Rmax*

Range	Resolution	Intrinsic Uncertainty	Measuring Uncertainty
0.100 to 9.999 MΩ	0.001 MΩ	(2% rdg. + 10 d)	(3 % rdg. + 20 d)
10.00 to 99.99 MΩ	0.01 MΩ	(2% rdg. + 10 d)	(3 % rdg. + 20 d)
100.0 to 999.9 MΩ	0.1 MΩ	(2% rdg. + 10 d)	(3 % rdg. + 20 d)
1.000 GΩ ... Rmax*	0.001 GΩ	(4 % rdg. + 15 d)	(5 % rdg. + 25 d)

* The Rmax value depends on the selected test voltage:

Nominal voltage of 50 to 99 V Rmax = 1.999 GΩ
 Nominal voltage of 100 to 249 V Rmax = 3.999 GΩ
 Nominal voltage of 250 to 1000 V Rmax = 9.999 GΩ

Nominal measuring voltage 50 to 1000 V adjustable in steps of 1 V
 Measuring voltage –0%/+10% of nominal voltage
 Nominal measuring current ≥ 1 mA (where Umes > Unom)
 Short-circuit current < 3 mA
 Automatic discharging of the DUT Yes
 Number of measurements approx. 250 (with new alkaline batteries)

Insulation Measuring Instrument

Measurement of Surge Protection Devices

Range	Resolution	Intrinsic Uncertainty	Measuring Uncertainty
40 to 1050 V	1 V	(2% rdg. + 2 d)	(3 % rdg. + 3 d)

Measuring Method Rising DC voltage when measuring the so-called milliampere point

Measurement of Direct and Alternating Voltage (Frequency Range: 45 to 60 Hz)

Range	Resolution	Intrinsic Uncertainty	Measuring Uncertainty
0 to 600 V	1 V	(2% rdg. + 2 d)	(3 % rdg. + 3 d)

Key

- a) The TRMS value for alternating voltage is measured.
- b) rdg. means reading, i.e. measured value.
- d = digits (i.e. number of the decimal place with the least significance)

Reference Conditions

Temperature	23 ± 2 °C
Relative humidity	40 to 60%
Device position	any

Ambient Conditions

Operating Conditions

Operating temperature	0 to 40 °C
Relative humidity	max. 85 %, no condensation allowed
Device position	any

Storage Conditions

Temperature	-10 to 70 °C
Relative humidity	max. 90% at -10 to +40 °C max. 80% at +40 to +70 °C
Device position	any

Power Supply

Batteries	4 ea. AAA (LR03), 1.5 V alkaline or 1.2 V NIMH (with at least 750 mAh)
Number of measurements	with batteries at 800 mAh: approx. 1,000 measurements (with 500 V test voltage on 500 kΩ)

Electrical Safety

Measuring category	with safety cap applied to test probe: CAT III 300 V without safety cap applied to test probe: CAT II 300 V
Pollution degree	2
Protection class	II

Electromagnetic Compatibility (EMC)

Interference emission	EN 61326-1:2006 class B
Interference immunity	EN 61326-1:2006

Mechanical Design

Display	OLED, multicolored, graphic
Protection	Housing: IP 43
Dimensions	approx. 260 x 70 x 40 mm
Weight	approx. 0.36 kg with batteries

Scope of Delivery

- 1 Test instrument with mobile test probe
- 1 Pouch
- 1 CD ROM with operating instructions in available languages
- 1 Condensed operating instructions

Order Information

Description	Type	Article number
Insulation measuring instrument	METRALINE ISOCHECK	M507C
Broad-range charger for charging optionally available batteries, e.g. Z507B, inserted in the METRALINE ISO-RCD-Z CHECK Input*: 100 to 240 V AC ±10%; Output: 9 V DC, 180 mA	Charger METRALINE CHECK Series	Z507A
4 rechargeable batteries (AAA) for METRALINE ISO-RCD-Z/CHECK	Akku-Set METRALINE CHECK Series	Z507B

* with plug adapter for the following countries: EU, UK, US, AU

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op euro-index.nl/diensten



Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.nl) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 21004



NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: 010 - 2 888 000
F: 010 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: +32 - (0)2 - 757 92 44
F: +32 - (0)2 - 757 92 64
info@euro-index.be
www.euro-index.be