

## 1. ELECTRICAL SPECIFICATIONS

Accuracy calculated as  $\pm[\% \text{reading} + (\text{num dgt} * \text{resolution})]$  ta 18°C ÷ 28°C, <75%RH

### DC VOLTAGE

Range	Resolution	Accuracy	Input impedance	Overload protection
600.0mV	0.1mV	$\pm(0.8\% \text{rdg} + 5 \text{dgt})$	>10M $\Omega$	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

### AC TRMS VOLTAGE

Range	Resolution	Accuracy (*) (50Hz ÷ 60Hz)	Accuracy (*) (61Hz ÷ 400Hz)	Overload protection
6.000V	0.001V	$\pm(1.0\% \text{rdg} + 8 \text{dgt})$	$\pm(2.0\% \text{rdg} + 8 \text{dgt})$	1000VDC/ACrms
60.00V	0.01V			
600.0V	0.1V			
1000V	1V	$\pm(1.2\% \text{rdg} + 8 \text{dgt})$	$\pm(2.5\% \text{rdg} + 8 \text{dgt})$	

(\*) Accuracy specified from 5% to 100% of measurement range  
Input impedance: >10M $\Omega$ , Crest factor:  $\leq 3$  (up to 500V),  $\leq 1.5$  (up to 1kV)

### DC/AC TRMS VOLTAGE WITH LOW IMPEDANCE (LoZ)

Range	Resolution	Accuracy (50Hz ÷ 400Hz)	Input impedance	Overload protection
600.0mV (*)	0.1mV	$\pm(0.8\% \text{rdg} + 5 \text{dgt})$	approx 3k $\Omega$	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

(\*) DC only

### DC CURRENT

Range	Resolution	Accuracy (*)	Overload protection
600.0 $\mu$ A	0.1 $\mu$ A	$\pm(1.0\% \text{rdg} + 3 \text{dgt})$	Fast Fuse 800mA/1000VAC/DC (inputs mA, $\mu$ A)
6000 $\mu$ A	1 $\mu$ A		
60.00mA	0.01mA		
600.0mA	0.1mA		
6.000A	0.001A	$\pm(1.5\% \text{rdg} + 3 \text{dgt})$	Fast Fuse 10A/1000VAC/DC (input 10A)
10.00A (*)	0.01A		

(\*) 20A for max 30s with not declared accuracy

### AC TRMS CURRENT


Range	Resolution	Accuracy (*) (40Hz ÷ 400Hz)	Overload protection
600.0 $\mu$ A	0.1 $\mu$ A	$\pm(1.5\% \text{rdg} + 8 \text{dgt})$	Fast Fuse 800mA/1000VAC/DC (inputs mA, $\mu$ A)
6000 $\mu$ A	1 $\mu$ A		
60.00mA	0.01mA		
600.0mA	0.1mA		
6.000A	0.001A	$\pm(2.0\% \text{rdg} + 3 \text{dgt})$	Fast Fuse 10A/1000VAC/DC (input 10A)
10.00A (**)	0.01A		

(\*) Accuracy specified from 5% to 100% of measurement range

(\*\*) 20A for max 30s with not declared accuracy



## DIODE TEST

Range	Max test current	Open voltage
	<0.9mA	2.8V

## RESISTANCE AND CONTINUITY TEST

Range	Resolution	Accuracy	Buzzer	Overload protection
600.0Ω	0.1Ω	±(1.0%rdg+4dgt)	<100Ω	1000VDC/ACrms
6.000kΩ	0.001kΩ			
60.00kΩ	0.01kΩ			
600.0kΩ	0.1kΩ			
6.000MΩ	0.001MΩ	±(2.0%rdg+10dgt)		
60.00MΩ	0.01MΩ			

## FREQUENCY (Electronic circuits)

Range	Resolution	Accuracy	Sensitivity	Overload protection
9.999Hz	0.001Hz	±(0.1%rdg+8dgt)	0.8Vrms min (20% < duty < 80%, <100kHz) 5Vrms min (20% < duty < 80%, >100kHz)	1000VDC/ACrms
99.99Hz	0.01Hz			
999.9Hz	0.1Hz			
9.999kHz	0.001kHz			
99.99kHz	0.01kHz			
999.9kHz	0.1kHz			
9.999MHz	0.001MHz			
40.00MHz	0.01MHz			

## FREQUENCY (Electrical circuits)

Range	Resolution	Accuracy	Sensitivity	Overload protection
10Hz ÷ 400Hz	0.001Hz	±(1.5%rdg+5dgt)	15Vrms 10Arms	1000VDC/ACrms

## DUTY CYCLE

Range	Resolution	Accuracy	Overload protection
0.1 ÷ 99.9%	0.01%	±(1.2%rdg+2dgt)	1000VDC/ACrms

Pulse width: 100μs ÷ 100ms ; Frequency: 5Hz ÷ 150kHz



## 2. GENERAL SPECIFICATIONS

### Display:

- LCD, 4dgt, 6000 counts, sign, decimal point and bargraph
- Automatic polarity indication
- Backlight
- "OL" over range indication
- Response time: 2/s
- Conversion: TRMS

### Features:

- Data HOLD
- MAX/MIN
- RANGE
- REL

### Power supply:

- 1x9V alkaline battery NEDA 1604 IEC 6F22
- Battery life: ca. 25h (backlight ON), ca. 50h (backlight OFF)
- Auto Power OFF after 15 minutes of idleness

### Mechanical specifications

- Dimensions (L x W x H): 175 x 85 x 55mm
- Weight (included battery): 360g
- Mechanical protection: IP40

### Environmental conditions:

- Working temperature: 5 °C ÷ 40 °C,
- Working humidity: <80%RH
- Storage Temperature: -20 °C ÷ 60 °C
- Storage humidity: <80%RH
- Altitude max of use: 2000m

### Reference guidelines:

- Safety : IEC/EN61010-1
- EMC : IEC/EN61326-1
- Pollution degree: 2
- Insulation: double insulation
- Measurement category : CAT IV 600V – CAT III 1000V

**This product conforms to the prescriptions of the European directive on low voltage 2014/35/EU and to EMC directive 2014/30/EU**

**This product conforms to the prescriptions of the European directive 2011/65/EU (RoHS) and the European directive 2012/19/EU (WEEE)**



# Diensten van EURO-INDEX

**EURO-INDEX is fabrikant van BLAUWE LIJN en importeur/distributeur van diverse A-merken test- en meetinstrumenten. Wij leveren naast instrumenten ook de diensten om het gebruik hiervan in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van meetinstrumenten.**

## Geautoriseerd Service Centrum

EURO-INDEX is van de meeste merken in ons assortiment een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument blijft intact, net als de certificering (ATEX, EN50379, etc.).

## Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij [accreditatienummer K105](#).



**Kijk voor een overzicht van al onze diensten op [euro-index.nl/diensten](http://euro-index.nl/diensten)**

## KWS®

KWS® is een unieke kalibratieformule voor uw test- en meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten.

Uw kalibratiecertificaten zijn digitaal beschikbaar via Mijn KWS (gratis webportaal en app) en door de QR-code te scannen van de kalibratiesticker op het instrument.

## Verhuur van meetinstrumenten

Er zijn diverse situaties waarbij huren handig is:

- U heeft tijdelijk extra toestellen nodig.
- Uw eigen meetinstrument wordt onderhouden en/of gekalibreerd.
- U moet een eenmalige meting verrichten.

## EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen, infosessies en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Kalibratielaboratorium

Wijzigingen voorbehouden EURO-INDEX® NL 26006



**NEDERLAND**  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
010 - 2 888 000  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)



**BELGIË**  
Leuvensesteenweg 607  
1930 Zaventem  
+32 - (0)2 - 757 92 44  
[sales@euro-index.be](mailto:sales@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)