



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

REFRIGERANT RECOVERY

CE



MADE IN USA

69000 REFRIGERANT RECOVERY SYSTEM

SPECIFICATIONS:

- 1/2 HP oil-less compressor
- Recovery Rate: • direct vapor up to 3/4 lb/m
• direct liquid up to 2 1/2 lb/m
• push-pull up to 12 lb/m
- Operating Temperature Range: 32 to 122°F
- Weight: 38 lbs / Dimensions: 17" L x 10" W x 12" H
- Refrigerants: CFC's, HCFC's, HFC's

FEATURES:

- High performance oil-less compressor
- High volume cooling fan design
- Automatic low pressure Cut-Off Switch
- Liquid compatible head-valve system
- Safety high pressure Cut-Off Switch
- Fully reinforced hard plastic casing

The professional recovery systems are compact, lightweight and work with all refrigerants. They're ideal for commercial, residential or industrial appliance applications. Our recovery systems offer a state-of-the-art 1/2 HP oil-less compressor with a built-in high volume cooling fan. This new innovative design delivers maximum cooling efficiency which keeps the compressor working at high capacities in even the hottest climates. The compressor is also protected by an automatic low pressure cut-off switch that shuts off the unit once the recovery is complete. This AUTO SHUT-OFF feature eliminates the risk of compressor failure and reduces the user's need to monitor the entire recovery system. All of our recovery systems offer our newest color-coded gauges with pressure readings in PSI, BAR and MPa. Our stainless steel ball valve designed manifold controls the flow smoothly and quickly with only a 1/4 turn. With all of this protected by a reinforced hard plastic case, Mastercool's recovery systems will meet all your refrigerant recovery needs.

CE



MADE IN USA

69100 COMPLETE A/C RECOVERY SYSTEM

SPECIFICATIONS:

- 69100: 115V – 60Hz / 69100-220: 220V – 50/60 Hz
- 1/2 HP Oil-less Compressor
- Recovery Rate: • direct vapor up to: 3/4 lb/m / .5 kg/m
• direct liquid up to: 2 1/2 lb/m / 1.4 kg/m
• push-pull up to: 12 lb/m / 5.5 kg/m
- Operating Temperature Range: 32-122°F (0 to 50°C)
- Refrigerants: All
- Weight: 38 lbs / Dimensions: 17" L x 10" W x 12" H (432mm x 254mm x 305mm)

FEATURES:

- High performance oil-less compressor
- High volume cooling fan design
- Automatic low pressure Cut-Off Switch
- Liquid compatible head-valve system
- Safety high pressure Cut-Off Switch
- Fully reinforced hard plastic casing

The 69100 Professional Recovery System is compact, lightweight and works with all refrigerants. It offers a state of the art 1/2 hp oil-less compressor with a built-in high volume cooling fan. This innovative design delivers maximum cooling efficiency which keeps the compressor working at high capacities in even the warmest climates. The compressor is protected by an automatic low Pressure cut-off switch that shuts off the unit once the recovery is complete. This auto shut-off feature eliminates the risk of compressor failure and reduces the user's need to monitor the entire recovery process. The 69100 also includes an oil separator and filter dryer to cleanse the refrigerant during the recovery process. The Mastercool Recovery System offers our newest color-coded gauges with pressure readings in PSI, BAR and MPa. The stainless steel ball valve designed manifold controls the refrigerant flow smoothly and quickly with only a 1/4 turn. All of the internal components have been arranged and isolated to ensure a smooth and quiet performance. With all of this protected by a reinforced hard plastic case, Mastercool's Recovery System will meet all of your refrigerant needs.

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op euro-index.nl/diensten



Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal (mijnkws.nl) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 21004



NEDERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: 010 - 2 888 000
F: 010 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: +32 - (0)2 - 757 92 44
F: +32 - (0)2 - 757 92 64
info@euro-index.be
www.euro-index.be