

## DPM1000 Power clamp



- AC/DC Voltage to 1000 V
- AC/DC Current to 1000 A
- True RMS
- Resistance 100 k $\Omega$
- LCD Display
- Phase rotation indication
- Inrush peak current
- Auto backlight display
- Frequency measurement
- Capacitance measurement
- Power Factor Measurement
- Watt measurement to 1 MW
- Harmonic measurement
- Harmonic distortion
- Diode test
- Non-contact volt alert
- Continuity Beeper
- Data Hold/Min-Max/Peak Hold
- Bright LED torch
- Temperature to 1000 ° C
- Carrying holster/pouch
- CAT IV 600 V Rating
- Bluetooth/Megger Link™ APP
- Supplied with carry case

### DESCRIPTION

The new Megger DPM1000 Power Clamp meter combines the functionality of power meter, harmonics meter and data logger in one easy to use package. The design meets the requirements of BSEN 61010-1 CAT IV 600 V for supply side applications. A large backlit LCD clearly displays all measurements that turns on at the touch of a button or when rotating the selection dial. It also automatically switches off to save battery consumption.

The DPM1000 can measure DC, AC, pulsed and mixed currents up to 1000 A simply by clamping the jaws around the appropriate conductor, whilst voltages up to 1000 V AC or DC may be measured by the supplied test leads. Where power measurements are to be made both techniques above are performed simultaneously. All power related parameters including energy consumption, frequency, total harmonic distortion, distortion factor and capacitance. It features auto-ranging and has 3 phase rotation indication.

The DPM1000 measures Single and 3 phase active power and power factor, the harmonic content of the signal, up to the 25th harmonic can be displayed. Temperature measurements can be made up 1000 °C using the thermocouple provided.

The DCM1000 is ideally suited to measuring mains power quality and applications in the development, installation, maintenance and repair of equipment and devices used in power electronics and power engineering. The unit has an internal torch that lights during the operation of the clamp and automatic non-contact voltage detection for identification of live circuits.

The DPM 1000 may be used to perform data logging to its internal non-volatile memory. You can record a maximum of 9999 readings/records to the memory over a period of time and download the data to produce graphs and reports. The record rate can be set from 1 sec to 600 sec. The accuracy of the timer is within 3 seconds per hour.

The meter uses low-power Bluetooth v4.0 wireless technology to transfer real-time data to the free Megger Link™ app, available for both iOS and Android. The maximum communication range in open air is approximately 10 m. This function is invalid for Inrush and Phase Rotation.

The DPM1000 is supplied complete with test leads and Thermocouple Probe in full sized Carry case.

## DPM1000 Power clamp

### SPECIFICATIONS

**ACA Range:** 0 A – 1000 A

- Resolution 0.01 A
- Basic Accuracy  $\pm (1.5\% + 5d)$  at 50-500 Hz
- Conversion Type AC+DC True-RMS

**ACV Range:** 0 V – 1000 V

- Resolution 0.01 V
- Basic Accuracy  $\pm (1.5\% + 5d)$  at 50 Hz~500 Hz
- Input Impedance 3.5 M $\Omega$
- Overload Protection: 1000 V rms

**DCA Range:** 0 A – 1000 A

- Resolution 0.01 A
- Basic Accuracy  $\pm (1.5\% + 5d)$

**DCV Range:** 0 V – 1000 V

- Resolution 0.01 V
- Basic Accuracy  $\pm (0.7\% + 2d)$
- Input Impedance 3.5 M $\Omega$
- Overload Protection: 1000 V rms

**AC+DCV Range:** 0 V – 1000 V

- Resolution 0.01 V
- Basic Accuracy  $\pm (1.7\% + 7d)$
- Input Impedance 3.5 M $\Omega$
- Overload Protection: 1000 V rms

**Watt:** 0 KW – 1 MW

- Resolution 1 W

**Power Factor:** -1.00 – 1.00

- Resolution 0.01
- Basic Accuracy  $\pm 5d$

**T.H.D:** 0.1% – 100%

- Resolution 0.1%
- Basic Accuracy  $\pm (3.0\% + 10d)$

**Harmonics:** 0.1% – 100%

- Resolution 0.1%
- Basic Accuracy  $\pm (5.0\% + 10d)$  For order 1-12  
 $\pm (10.0\% + 10d)$  For order 13-25

**Resistance:** 0  $\Omega$  – 100 k $\Omega$

- Resolution 0.01  $\Omega$
- Basic Accuracy  $\pm (1.0\% + 5dgt)$
- Overload Protection: 1000V rms

**Continuity Beeper:** <30  $\Omega$ , 2 KHz tone buzzer

**Diode Test:**

- Open Circuit Voltage:  
 $\pm 1.8$  V max

**Capacitance:** 4  $\mu$ F – 4000  $\mu$ F

- Resolution 1 nF
- Basic Accuracy  $\pm (1.9\% + 8d)$
- Overload Protection: 1000 V rms

**Frequency Counter:** 20.00 Hz – 10.00 KHz

- Resolution 0.01 Hz
- Accuracy  $\pm 0.5\% + 3d$

**Temperature:** -50°C – 1000°C

- Resolution 0.1°C
- Accuracy  $\pm (1.0\% + 3^\circ\text{C})$
- Overload Protection: 1000 V rms

**Sampling Rate:** 3 times/sec

**Overload Indication:** "OL" or "-OL"

**Low Battery Indication**

**Auto Power Off:** 15 Minutes

**Operating Temperature:** 0°C – 50°C,  $\leq 80\%$  RH

**Storage Temperature:** -10°C – 50°C

**Temperature Coefficient:**

0.2 x (Spec. Acc)/°C,  
<18°C or >28°C

**International Standard:** IEC/EN 61243-3:2014

**Safety Standard:** IEC 61010-1, Designed to meet  
UL61010 Spec CAT IV 600V,  
CAT III 1000 V

**Maximum Conductor**

**Size:** 40 mm

**Maximum Busbar Size:** 61 x 12mm

**Power Requirement:** AAA Size Battery 1.5V x 6

**Battery Life in hours:** 50

**Size:** 103 mm(W) x 258 mm (L)  
x 55 mm(H)

**Weight: (with battery)** 600 g

Specification subject to change without notice

# DPM1000

## Power clamp

### ORDERING INFORMATION

Description	Part number
<b>DPM1000 power clamp meter</b>	<b>1013-356</b>
<i>Included accessories</i>	
DCM 4 mm Spare Lead Set	1013-358
TP100 K-Type Thermocouple Probe	1013-364
Hard Carry Case	

#### SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T +44 (0) 1304 502101  
E UKsales@megger.com

#### DPM1000\_DS\_en\_V05

www.megger.com  
ISO 9001  
The word 'Megger' is a registered trademark

**Megger**<sup>®</sup>

# Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op [euro-index.nl/diensten](http://euro-index.nl/diensten)



## Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over een laboratorium op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

## KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Via een gratis webportal ([mijnkws.nl](http://mijnkws.nl)) heeft u altijd en overal beschikking over uw kalibratiecertificaten.

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

## EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 21004



NEDERLAND  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: 010 - 2 888 000  
F: 010 - 2 888 010  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)



BELGIË  
Leuvensesteenweg 607  
1930 Zaventem  
T: +32 - (0)2 - 757 92 44  
F: +32 - (0)2 - 757 92 64  
[info@euro-index.be](mailto:info@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)