

# TDR1000/3P

## Handheld TDR



- **Simple operation**
- **AUTO set up for instant use**
- **Ultra fast pulse for near end fault identification**
- **Trace HOLD feature to allow comparison between cables**
- **IP54 rating offers real life working**
- **Designed for use on all metallic cable pairs**

---

### DESCRIPTION

The TDR1000/3P is a hand held, compact Time Domain Reflectometer for locating faults on metallic cables. It has a minimum resolution of 0.1 m/0.3 ft and a 5 km/15 kft maximum range depending on velocity factor selected and cable type.

Four output impedances are available (25, 50, 75, and 100  $\Omega$ ) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements

The TDR1000 has a simple selection option which together with a 4 way control switch offers an intuitive operation for the user.

### FEATURES AND BENEFITS

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. Dual cursors allow complete flexibility, giving the operator full control and instant indication of distance between two points.

A trace HOLD feature also allows comparison between conditions, something not seen on most other handheld TDRs. Extra high resolution together with white-light backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.

- Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 0.1 m
- For use on Telecom TNV-3 circuit, or 150 V CAT IV power circuits
- Power blocking filter not required
- Environmental protection to IP54
- Auto selected output impedance (between 25, 50, 75 and 100  $\Omega$ )
- 2 ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- Display distance in metres or feet
- Uses five AA (LR6) primary cells

## SPECIFICATIONS

<b>Range</b>	10 m, 25 m, 100 m, 250 m, 1000 m, 2500 m, 5000 m (30 ft, 75 ft, 300 ft, 750 ft, 3000 ft, 7500 ft, 15000 ft)
<b>Accuracy</b>	±1% of range ± pixel at 0.67 VF [Note- The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.]
<b>Resolution</b>	1% of range
<b>Input protection</b>	This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV when used with the supplied fused test lead set.
<b>Output pulse</b>	5 volts peak to peak into open circuit. Pulse widths determined by range and cable
<b>Gain</b>	Set for each range with three user selectable steps (in Manual operating mode)
<b>Velocity factor</b>	Variable from 0.2 to 0.99 in steps of 0.01
<b>TX null</b>	Automatic
<b>Power down</b>	Automatic after 5 minutes with no key press
<b>Backlight</b>	Stays on for 1 minute with no key press
<b>Battery</b>	Five LR6 (AA) type batteries, Manganese alkali or nickel metal-hydride cells
<b>Battery life</b>	Up to 14 hours (Typical)
<b>Dimensions</b>	230 x 115 x 48 mm ( 9.0 x 4.5 x 2.0 inches)
<b>Weight</b>	0.6 kg (1.32 lbs)

<b>Case</b>	ABS
<b>Connectors</b>	Two 4 mm-safety terminals
<b>Test lead</b>	(19 mm spaced TDR1000/3P): 1 pair 1.5 m retractable sheath, fitted with 500 mA FF HBC 1 kV 50 kA fuse
<b>Display</b>	256 x 128 pixel Graphics LCD
<b>Operating temperature range and humidity</b>	-15 °C to +50 °C (5 °F to 122 °F)
<b>Storage temperature range and humidity</b>	-20 °C to 70 °C (-4 °F to 158 °F)
<b>Safety</b>	When using the supplied fused test lead set this instrument complies with IEC61010-1 for connection to live systems with less than 300 V between the terminals and up to 150 V CAT IV to earth
<b>EMC</b>	Complies with Electromagnetic Compatibility Specifications (Light industrial) BS EN 61326-1, with a minimum performance of 'B' for all immunity tests

## ORDERING INFORMATION

Description	Part number	Description	Part number
Time Domain Reflectometer	1001-789	<b>Included accessories</b>	
		Hard case	
		User guide CD	
		Retractable sheath fused test lead (1 pair)	
		<b>Optional accessories</b>	
		Miniature clip test lead set (1 pair)	6231-652
		Red and black probes and clips - for use with all Megger TDR Fused Test Leads.	1002-491
		Split conductor fused test lead set (1 pair)	1002-015

# Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

## Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

## Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op [euro-index.nl/diensten](http://euro-index.nl/diensten)



## Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over laboratoria op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

## KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Uw kalibratiecertificaten zijn digitaal beschikbaar via Mijn KWS (gratis webportaal en app).

## Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

## EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 24005



NEDERLAND  
Rivium 2e straat 12  
2909 LG Capelle a/d IJssel  
T: 010 - 2 888 000  
F: 010 - 2 888 010  
[verkoop@euro-index.nl](mailto:verkoop@euro-index.nl)  
[www.euro-index.nl](http://www.euro-index.nl)



BELGIË  
Leuvensesteenweg 607  
1930 Zaventem  
T: +32 - (0)2 - 757 92 44  
F: +32 - (0)2 - 757 92 64  
[info@euro-index.be](mailto:info@euro-index.be)  
[www.euro-index.be](http://www.euro-index.be)