

Technical data sheet

Multitec[®] 520

Device data	
Dimensions (W x D x H)	approx. 148 x 57 x 205 mm approx. 148 x 57 x 253 mm with supporting bracket
Weight	approx. 1000 g, depending on equipment

Certificates	
Certificate	TÜV 07 ATEX 553353 X II2G Ex d e ib IIB T4 Gb basic device without leather bag for: CH ₄ , C ₃ H ₈ , C ₄ H ₁₀ , C ₉ H ₂₀ , H ₂ S, CO II2G Ex d e ib IIC T4 Gb basic device with leather bag for: CH ₄ , C ₃ H ₈ , C ₄ H ₁₀ , C ₉ H ₂₀ , H ₂ S, CO, H ₂ BVS 09 ATEX G 001 X, PFG 08 G 002 X (applies to CH ₄ , C ₃ H ₈ , C ₉ H ₂₀ , CO ₂ , O ₂ , CO, H ₂ S)

Device elements	
Display	monochromatic graphic display, 320 x 240 pixels
Buzzer	frequency 2.4 kHz, volume 80 db (A) / 1 m
Signal light	red
Pump capacity	vacuum > 250 mbar, volume flow approx. 50 l/h
Interface	USB
Memory	8 MB
Operation	ON/OFF key, 3 function keys, jog dial

Operating conditions	
Operating temperature	-20 °C – +40 °C
Storage temperature	-25 °C – +60 °C (temperatures above 40 °C reduce the lifetime of the sensors)
Humidity	5 – 90 % r.h., non-condensing
Atmospheric pressure	950 – 1100 hPa
Protection rating	IP54

Power supply	
Power supply	NiMH rechargeable or disposable alkaline batteries, type Mignon (AA)
Operating time, typical	at least 8 h
Charging time	approx. 3 h (complete charge) depending on capacity
Charging voltage	12 V DC, max. 1 A

Data transmission	
Communication	USB

Gas types	
Standard	methane CH ₄
Optional	propane C ₃ H ₈ butane C ₄ H ₁₀ nonane C ₉ H ₂₀

Infrared sensor C_xH_y	
Measuring range	0 – 4.4 % vol. (CH ₄), 0 – 100 % LEL
Resolution	0.05 % vol.
Response times	t ₅₀ < 8 s (CH ₄), t ₉₀ < 14 s (CH ₄)
Warm-up time	17 s
Measuring error	±1 % LEL (short-term stability as per EN 60079-29-1) ±4 % LEL (long-term stability as per EN 60079-29-1)
Interference	all hydrocarbons
Lifetime, expected	5 years

Infrared sensor CO₂	
Measuring range	0 – 5 % vol.
Resolution	0.02 % vol.
Response times	t ₉₀ < 20 s
Warm-up time	17 s
Measuring error	±0.04 % vol. (long-term stability as per EN 45544)
Interference	none
Lifetime, expected	5 years

Electrochemical sensor oxygen O2	
Measuring range	0 – 25 % vol.
Resolution	0.1 % vol.
Response times	t ₉₀ < 15 s
Warm-up time	approx. 1 min
Temperature range	-20 °C – +40 °C
Measuring error	±3 % or ±0.3 % vol. (±3 digits)
Interference	none
Lifetime, expected	36 months

Electrochemical sensor carbon monoxide CO	
Measuring range	0 – 500 ppm
Resolution	1 ppm
Response times	t ₉₀ < 30 s
Warm-up time	approx. 1 min
Temperature range	-20 °C – +40 °C
Measuring error	±10 % or ±3 ppm (±3 digits) ±5 ppm (long-term stability as per EN 45544)
Interference	at 20 °C – 3000 ppm H ₂ : approx. 1000 ppm CO – 100 ppm NO: approx. 25 ppm CO
Lifetime, expected	36 months

Electrochemical sensor hydrogen sulphide H2S	
Measuring range	0 – 100 ppm
Resolution	1 ppm
Response times	t ₉₀ < 30 s
Warm-up time	approx. 1 min
Temperature range	-20 °C – +40 °C
Measuring error	±10 % or ±3 ppm (±3 digits) ±2 ppm (long-term stability as per EN 45544)
Interference	– 100 ppm CO: approx. 1 ppm H ₂ S – 1 % vol. H ₂ : approx. 10 ppm H ₂ S – 100 ppm NO ₂ : approx. 3 ppm H ₂ S
Lifetime, expected	36 months

Electrochemical sensor ammonia NH₃	
Measuring range	0 – 100 ppm
Resolution	1 ppm
Response times	t ₉₀ < 60 s
Warm-up time	approx. 1 min
Temperature range	-20 °C – +40 °C
Measuring error	±10 % or ±3 ppm (±3 digits)
Interference	H ₂
Lifetime, expected	24 months

106658 – 06-06-2012 – Subject to technical changes.

Diensten van EURO-INDEX

EURO-INDEX is fabrikant, importeur en distributeur van diverse A-merken op het gebied van test- en meetinstrumenten. Daarnaast leveren wij een groot aantal diensten om het gebruik van deze instrumenten in uw bedrijfsvoering te optimaliseren. Dit omvat uiteraard onderhoud, reparatie en kalibratie van de instrumenten, maar ook kennisdeling via de EURO-INDEX Academy en verhuur van instrumenten.

Geautoriseerd Service Centrum

EURO-INDEX b.v. is van alle vertegenwoordigde merken een Geautoriseerd Service Centrum. Dit betekent dat uw instrumenten worden behandeld door technici die zijn opgeleid door de fabrikant en beschikken over de juiste gereedschappen en software. Er worden uitsluitend originele onderdelen toegepast en de garantie van uw instrument, evenals de certificering (ATEX, EN50379, etc.) blijven intact.

Kalibratielaboratorium

Ons moderne service- en kalibratielaboratorium beschikt over een RvA accreditatie naar NEN-EN-ISO/IEC 17025. Deze accreditatie geldt voor grootheden, zoals gespecificeerd in de scope bij accreditatienummer K105.



Kijk voor een overzicht van al onze diensten op euro-index.nl/diensten



Mobiele Service

Naast de vaste kalibratielaboratoria in Capelle aan den IJssel en Zaventem beschikken wij ook over laboratoria op wielen met de naam "Mobiele Service". Dit biedt vertrouwde service en kwaliteit, bij u voor de deur!

KWS®

KWS® is een uniek servicesysteem voor uw meetinstrumenten met periodiek onderhoud en kalibratie tegen vaste, lage kosten. Uw kalibratiecertificaten zijn digitaal beschikbaar via Mijn KWS (gratis webportaal en app).

Verhuur van meetinstrumenten

- Uitgebreid assortiment
- Nauwkeurigheid aantoonbaar door actueel kalibratiecertificaat
- Deskundig advies
- Complete levering inclusief accessoires

EURO-INDEX Academy

- Trainingen (individueel en klassikaal)
- Cursussen en workshops
- Demonstratie- en instructievideo's
- Whitepapers



Servicebalie



Onderhoud, reparatie en kalibratie



Cursussen en workshops



Mobiele Service

Wijzigingen voorbehouden EURO-INDEX® NL 24005



NETHERLAND
Rivium 2e straat 12
2909 LG Capelle a/d IJssel
T: 010 - 2 888 000
F: 010 - 2 888 010
verkoop@euro-index.nl
www.euro-index.nl



BELGIË
Leuvensesteenweg 607
1930 Zaventem
T: +32 - (0)2 - 757 92 44
F: +32 - (0)2 - 757 92 64
info@euro-index.be
www.euro-index.be